



Driver: _____ Clay Hard Packed Loose Dirt
 Date: _____ Carpet Asphalt Concrete
 Event: _____ Flat Banked True Oval Tri-Oval
 Class: _____
 Track: _____ Length: _____ Traction: High Medium Low

FRONT SUSPENSION

-Shade in locations of suspension arms and camber links on the shock tower.

Toe IN / OUT _____

Sway Bar: None .063" .078"

LEFT RIGHT

Camber: _____ Caster: _____

Link Position: Ball Stud Caster Block

Camber Rate Shims: _____

Front Axle: Stock Extended Axle Spacing Shims: _____

Roll Center: High Low

Camber Rate Shims: _____

Front Axle: Stock Extended Axle Spacing Shims: _____

SHOCKS

Spring	Oil	Piston	Length	Limiters	Collar
RF: _____	_____	_____	_____	_____	_____
LF: _____	_____	_____	_____	_____	_____
RR: _____	_____	_____	_____	_____	_____
LR: _____	_____	_____	_____	_____	_____

Corner Weights: LF: _____ RF: _____ LR: _____ RR: _____

Chassis Heights by Location: LF: _____ RF: _____ LR: _____ RR: _____

Measured From: Top of Chassis Bottom of Chassis

Overall Weight: _____

TIRES

Foam Street Rubber Buggy

Compound	Insert	Wheel	Diameter
RF: _____	_____	_____	_____
LF: _____	_____	_____	_____
RR: _____	_____	_____	_____
LR: _____	_____	_____	_____

Notes: _____

Traction Additive: _____

-Shade in Areas of Traction Additive and Draw in Tire Grooves

LF

RF

LR

RR

REAR SUSPENSION

-Shade in locations of suspension arms and camber links on the shock tower and bearing carrier.

LEFT RIGHT

Camber: _____ Toe-In: _____

Axle Spacing: _____

Hub Spacing:

Toe-Block Height: LR: _____ RR: _____

Anti-Squat Shims: LR: _____ RR: _____

Camber: _____ Toe-In: _____

Axle Spacing: _____

Hub Spacing:

MISC...

Battery Location: _____

Motor: _____

Pinion: _____ Spur: _____

Modified Late Model

Driver Comments: _____

"C"

"A"

Body: _____

Spoiler: _____

"B" Side Dam "A": _____

Side Dam "B": _____

Side Dam "C": _____

"C"

"A"